



YUH FARN

Advance your power

RIP SAW

Precision Engineered
to Ensure Lifetime
Straight Accuracy.



YFER-303S

SPECIFICATIONS 規格表

Maximum working thickness	最大加工厚度	85mm
Sawblade diameter	鋸片直徑	200-303mm(160mm optional)
Distance from blade to arm	鋸片至機身距離	400mm
Table surface area	工作台面尺寸	1310x780mm
Feed speed	送料速度	15 / 20 / 25 m/min
Saw arbor diameter	主軸直徑	Ø25.4mm
Saw arbor motor	主軸馬達	10HP (15HP optional)
Feed motor	送料馬達	1HP (2HP)
Saw arbor speed	鋸片轉速	4200 rpm
Dust exhaust outlet diameter	集塵罩出口徑	5"
Width of chain block	履帶寬度	140mm
Net weight	淨重	900kgs
Gross weight	毛重	1050kgs
Machine dimensions (LxWxH)	機械尺寸(長x寬x高)	1400x1020x1338mm
Packing dimensions (LxWxH)	裝箱尺寸(長x寬x高)	1500x1100x1500mm

*We reserve the right to modify design without prior notice.
*本公司保留機械設計變更之權力，恕不另行通知。

OPTIONAL EQUIPMENT 選購配備

- ▶ Infinitely Variable speed of chain feed.
- ▶ 無段送料速度



YUH FARN MACHINERY INDUSTRIAL CO., LTD.

NO.51, ALLEY 2, LANE 66, JIAO TAN ROAD, SEC.2, FENG YUAN, TAIWAN.

TEL:886-4-2528-2910, 2528-8863

FAX:886-4-2525-4171

E-MAIL: yuhfarn@ms32.hinet.net

http://www.yuhfarn.com.tw

http://www.woodsawing.com

YF HEAVY DUTY STRAIGHT LINE RIP SAW

精密鋸軸



Precision saw arbor assembly

- ▶ The saw arbor assembly is precision and ruggedly constructed to ensure precision
- ▶ Pressure roller and saw arbor assembly are conveniently raised and lowered by separate handwheel.

昇降壓料厚度鋼爪套 (附圖)



An elevator feeding rollers clamp thickness of numerals


無段變速 (選購)



Variable feed speed device(option)

- ▶ The device provides wide range of chain feed
- ▶ This permits the machine to cut all types of wood material, soft or hard.

鋸齒狀鏈片



Teeth of chain block

- ▶ Block surface is corrugated machined and hardened to resist wear
- ▶ Feed chain is absolutely aligned with sawblade, permitting for positive feeding of stock.

FEATURES

- ▶ Base is ruggedly fabricated to provide a solid foundation and vibration free cutting.
- ▶ End table swings downward and prevents short workpieces and thin edgings from sliding.
- ▶ Double anti-kickback fingers provide maximum operator safety.
- ▶ The sawblade is easily accessed for replacement.
- ▶ Control panel located within easy reach position for operation convenience.
- ▶ Chain blocks are linked by hardened steel pins.
- ▶ The automatic lubricator provides the correct amount of oil to lubricate the track slideways.
- ▶ This machine produces accurate edge for high accuracy glue joint.
- ▶ 400mm capacity from blade to arm.
- ▶ 3 feed speeds standard. Variable feed speed is optional.
- ▶ Powerful 10HP motor drive (15HP optional)

3重防反彈設計



Triple anti-kickback fingers

- ▶ Triple anti-kickback fingers provide maximum operator safety.

安全保護裝置設計



Complete safety protection

- ▶ Double top.
- ▶ 2 rollers clamp, 3 rollers(optional)
- ▶ 壓輪: 標準有2個 (3個為選購)

自動潤滑



Automatic lubricator

- ▶ The automatic lubricator provides the correct amount of oil to lubricate the track slideways, ensuring smooth chain motions at all time.



YFR-303S